



TROYLUBE

Motor Oils and Lubricants

TROYLUBE *ARMOR*

15W/40 CF-4/SG

TROYLUBE ARMOR 15W/40 is engine oil produced by blending high quality base oils with advanced performance additives. Provides complete lubrication in pickups, minibuses, agricultural machinery, work machines and generators with turbocharged and naturally aspirated diesel engines. It can also be used in vehicles operating with fuels such as gasoline and LPG.

Properties

- Extends oil change intervals by keeping the engine clean even in high sulfur fuel use.
- Provides easier first start thanks to its superior fluidity at low temperatures.
- Provides high engine power by minimizing friction inside the engine thanks to its active lubrication feature.

Approvals and Specifications

- API CF-4/SG
- ACEA A3/B3-04
- Caterpillar TO2
- MTU Level 1
- Volvo VDS
- MB 228.1, 229.1
- ACEA E3-96 Issue 4
- MAN 271
- Allison C4
- VW 501.01 – 505.00

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	12,5 - 16,3
Viscosity Index	ASTM D2270	Min. 120
Flash Point, °C	ASTM D92	Min. 230
Pour Point, °C	ASTM D97	Max. -24
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,5